



MATERIAL SAFETY DATA SHEET

Original Release Date: 0724/08

Issue: 1

Revised Date:

Section I - Company / Product Identity

Product Identification: Color " C_Cyan " - replacement cartridge for HP LaserJet 4700, 4730, 4005 **TG95P6497 (4700)**

Company : Turbon International GmbH
Ruhreich 10
D-45525 Hattingen

HMIS Hazard Rating:
0 = Minimal 3 = Serious
1 = Slight 4 = Severe
2 = Moderate

NFPA Hazard Rating:
0 = Minimal 3 = Serious
1 = Slight 4 = Extreme
2 = Moderate

Telephone: Germany +49-(0)2324-504-471
Fax: +49-(0)2324-504-133
Contact Person: Mr. Rob Aukema

HMIS Rating :	
Health	= 1
Flammability	= 1
Reactivity	= 0
PPE	= Section VIII

NFPA Rating :	
Health	= 1
Flammability	= 1
Instability	= 0
Special	= None

Section II - Composition / Ingredients

This product consists of new and remanufactured parts that are originally manufactured by the OEM.

The cartridge consists of light sensitive drum, toner , a developer unit and several blades.

Main components:

Plastics: PE, PP, PS, ABS, PU, Acetal, mixed with FR
Metals: Iron, Sheet steel. Some components electrolyze nickel-plated.
Non-metals: Aluminum
Foam: Expanded polyuthane, polyester base
Elastomer: Polyurethane

The toner used in this cartridge consists of the following components.

<u>Description</u>	<u>CAS number</u>	<u>Percent</u>	<u>R+S phrase</u>	<u>Symbol</u>
Blue Pigment	Proprietary	1 - 20	None assigned	None assigned
Silica, amorphous	Proprietary	< 5	None assigned	None assigned
Styrene Acrylate Copolymer	Proprietary	70-95	None assigned	None assigned

The drum used in this cartridge consists of the following components.

<u>Description</u>	<u>CAS number</u>	<u>Percent</u>	<u>R+S phrase</u>	<u>Symbol</u>
Substrate: Al-cylinder	None assigned	> 99%	None assigned	None assigned
Coating: Organic photoconductor	None assigned	< 1%	None assigned	None assigned

MATERIAL SAFETY DATA SHEET

Section III - Hazards Identification

Primary entry routes:

Inhalation :	Slight irritation of respiratory tract
Ingestion:	NA
Skin contact:	Repeated contact may cause irritation or an allergic skin reaction.
Eyes effects:	Dust may cause irritation by mechanical abrasion
Chronic effects:	If use generates airborne particles, treat as a Nuisance Particulate (ACGIH TLV = 10mg/cu meter)

Potential environmental hazard:

No particular hazards known. The cartridge is made in accordance with all known legal requirements.

Section IV - First Aid Measures

Inhalation:	Remove person to fresh air. If symptom's persists consult a physician.
Ingestion:	Rinse mouth with water and drink one or two glasses of water. If symptoms occur, call a physician. If symptom's persists, consult a physician.
Skin contact:	Wash well with soap and running water. If symptoms occur, call a physician.
Eyes contact:	Immediately flush with large amounts of clean lukewarm, low pressure water for at least 30 minutes. If irritation persists, consult a physician. Remove any contact lenses to facilitate flushing.

Section V - Fire and Explosion Measures

Flash point:	No data available.
Ignition temperature:	No data available.
Flammability	Slight (HMIS, NFPA)
Flammability limits	No data available.
Extinguishing media:	Water Fog, foam, CO ² , dry chemicals, or halon-type extinguishers.
Special fire fighting procedures:	To avoid inhalation of toxic fumes, wear MHSA/NIOSH approved self-contained breathing apparatus. Do not release runoff from fire control methods to sewers or waterways.
Un-usual fire / explosion hazards:	Toner may cause a dust explosion. Explosive limits of toner particles suspended in air are equal to coal dust.

Section VI - Accidental Release Measures

Spill and leakage procedures:	Wear personal protective equipment. Avoid breathing dust. Minimize the release of particles. Vacuum or sweep the material into a bag or other sealed container. If a vacuum cleaner is used, the motor must be rated as dust tight. Dispose of waste toner in accordance with local requirements.
Environmental precautions:	Do not discharge into drains.

Section VII - Handling and Storage

Advise on safe handling and protection against fire:

Keep material out of reach of children. Avoid inhalation of dust and contact with eyes. Keep away from excessive heat, sparks and open flames.

Requirements for storage rooms and advise on storage compatibility:

Keep out of reach of children. Keep container closed and store at room temperature. Keep away from strong oxidizers.

MATERIAL SAFETY DATA SHEET

Section VIII - Exposure Limits / Personal Protection

USA OSHA (TWA) / PEL:	15 mg/m ³ (Total Dust) 5 mg/m ³ (Respirable Fraction)
ACGIH (TWA / TLV)	10 mg/m ³ (Inhalable Particulate) 3 mg/m ³ (Respirable Particulate)
DFG (MAK)	6 mg/m ³ (Dust Concentration)
	In Canada, consult local authorities for acceptable provincial values.
Respiratory protection:	Not required under intended use.
Ventilation:	General ventilation should be sufficient under intended use.
Protective gloves:	Not required under intended use.
Eye protection:	Not required under intended use.
Other protective equipment:	Not required under intended use.

Section IX - Physical and Chemical Properties

Boiling point:	Not applicable
Melting point:	100° -150° Celsius
Particle size:	Fine
Vapor pressure:	NA
Solubility in water:	Negligible
Other Solubility's:	Partial soluble in Toluene & Xylene
Vapor density (air =1)	Heavier than air
Evaporation rate:	Not applicable
Color:	Cyan
Appearance:	Fine powder
Odor:	Faint

Section X - Stability and Reactivity

Stability:	Stable under conditions of normal use
Incompatibility:	NA
Hazardous decomposition products:	Combustion will produce carbon dioxide and possibly toxic chemicals such as carbon monoxide.
Hazardous polymerization:	Will not occur.

MATERIAL SAFETY DATA SHEET

Section XI - Toxicological Information

Toxicological info according to OSHA Hazard communication standard and commission directive 67/548/EEG.

Toner:	Ames test:	Negative. LD50 > 5000 mg/kg
	Ingestion:	Not toxic.
	Eye contact:	Not toxic.
	Skin contact:	Not toxic.
	Chronic toxicity:	No data available.
	Carcinogenicity:	Not expected to be carcinogenic
	Chronic health hazard comments	No known health hazard when used as intended in printer
	Exposure limit:	Not known.
	Inhalation:	Not toxic.
Drum:	Ames test:	Negative. (mutagenicity test from Prof. Ames, Berkeley University California, USA)
	Ingestion:	Not toxic.
	Eye contact:	Not toxic.
	Skin contact:	Not toxic.
	Chronic toxicity:	Not toxic.
	Carcinogenicity:	Not known.
	Chronic health hazard comments	None.
	Exposure limit:	Not known.
	Inhalation:	Not toxic.

Section XII - Ecological Information

Avoid spills and dispose of in accordance with applicable laws and regulations.

Section XIII - Disposal Considerations

Observe all federal, regional, and local regulations when disposing of the product.

Contact your local Turbon dealer for returning your used and empty cartridges.

Tel: 800 -282-6650

Fax: 800 -257-1619

Section XIV - Transport Information

International transport information:

UN no.:	None
UN shipping name:	None
Hazards class:	None
Packing group:	None
Special precautions:	None

MATERIAL SAFETY DATA SHEET

Section XV - Other Information

New components are purchased from international reputable producers. The information in this MSDS is based on our present state of knowledge.

In normal use there are no exceptional health, safety or fire hazards associated with this range of products. Please obey the usage and storage instructions.

This product is distributed, manufactured, and sold by Turbon. IBM, the IBM logo, the IBM trademarks and IBM Trade Dress are owned by International Business Machines Corporation and are used under a license from IBM.

Disclaimer: Judgements as to the suitability of information herein are the purchaser's responsibility. Although reasonable care has been taken in the preparation of such information, The Turbon Group extends no warranties, makes no representations, and assumes no responsibility as to the accuracy or suitability of such information for application to the purchaser's intended purpose or for the consequences of its use.